



IQLOCK-PG

PowerG Where it Matters




Better Range

Stable wireless communication over long range applications.



High Strength

ANSI Grade 2 certifications brings extra security and peace of mind.



Easy Installation

Easy configuration for smart locks with PowerG wireless communication.



Attractive Styling

Three finish options to allow for the best style fit on different door colors.



Reliable Connectivity

Reduce truck rolls by eliminating unstable wireless network connections.



PowerG

DSC



SPECIFICATIONS

Self-Handing	Supported
Bolt Type	Motorized / Standard deadbolt
Backset	2 3/8" / 2 3/4" Adjustable (60/70mm)
Door Prep	1 1/2" / 2 1/8" (38/54mm)
Door Thickness	1 3/8" ~ 2 1/4" (35-58mm) automatic adjustment
Unlocking Method	PowerG wireless communication (via App and Panel), Button keypad, key, thumb-turn
Code Capacity	User code x 250
Code Length	4-8 digits
Override Key Cylinder	Yes
Cylinder	KW1 keyway
Working Voltage	DC 6V
Battery (Not included)	AA x 4
Working Temperature	Exterior: -31°F to 151°F (-35°C to 66°C) Interior: 32°F to 140°F (0°C to 60°C)
IP Rating	Exterior assembly: IP54
Lockout Mode (Wrong entry limit)	Keypad lockout for 3 minutes after 10 entires of invalid user code
Low Battery Alarm	Yes
Battery Life	Min. 12 months (6 user code unlock events, and 10 unlocking and lock cycles for each day)
Certifications	FCC, IC, ANSI BHMA A156.36 Grade 2, UL10C (20min Fire Rating)
IoT Connection	PowerG
Product Weight	1.6KG/PCS (3.6 LB)
Operating Humidity	Exterior: 100% condensing Interior: 20% - 95% non-condensing

Product Details

SPECIFICATIONS

PART NUMBER

IMAGE

Matted Black

IQDLK-PGK-MB



Satin Nickel

IQDLK-PGK-SN



Oil Rubbed Bronze

IQDLK-PGK-ORB



PowerG

DSC

